

1. Technical infosheet

Description: G333p is a Graphic Rapid Solid Fixer based on Ammonium Thiosulfate in an Acid solution.

Applications: Used for fixing op Recording-, Camera-, Contact films

Used in combination with:

Replenisher: G333p

Developers: Most Graphic developers as there are: G101c, ACD, ASD

Using conditions: **Dilution:** (mixing device necessary)
 As a fixer solution: 1 pack G333p makes 20 litres
 As a fixer replenisher: 1 pack G333p makes 20 litres
 Fixing time: depending of film material and fixer condition between 8 and 20s.
 Fixing temperature: 30 to 35°C / 86 to 95°F

Replenishment:

Material	Without electrolytic treatment			With electrolytic treatment		
	Positive	50%bl	Neg	Pos	50%Bl	Neg
FILM	850	500	150	210	125	100

Storage conditions: always store G333p in an frost-free and dry environment.

Shelf life: 36 months after manufacturing

Physical properties: Specific weight: 160.65 grams product per liter/ 3213 grams /20 liters (=1 pack)
 pH: disolverd: 5.3

Sales packaging: :

chemistry	ABC code	Packaging	Dilution
G333p	EV8V5	5 pack for x 20 l (total 100 l)	1 pack makes 20 litres

Flap bags can be used in AgfaSolid "tilting trays".

Precautions: avoid contact with skin. After contact rince thouroughly with water.
 Read the MSDS (Material Safety Data Sheet)