



C323 – Euro Ink Stripper Methchloride Free **Technical Datasheet**

Date: 15/07/2013

Description

A fast evaporating manual ink cleaner with excellent solvency on a variety of ink types.

Properties

- Fast evaporating
- Flashpoint ~40C (All category solvent)
- Methylene Chloride free – no carcinogenic association like the industry standard Dichloromethane based versions.
- High ink solvency on most ink types cleans quickly and effectively, even on hardened ink deposits.
- Non aromatic formulation meaning its less aggressive on rollers and blankets.
- Suitable for most conventional roller qualities
- Non-marine pollutant – based on biodegradable raw materials
- VOC = 775grams/litre (90%).

Method of Use

- For manual use it can be pre-diluted with water depending on customers' preferences. Apply to a lint free cloth or sponge and wipe over the affected area. Finish by wiping with water using a separate cloth and allow to dry before restarting.
- Suitable for most modern day machines including manufacturers such as Heidelberg, KBA, Man Roland, Ryobi, Komori and Mitsubishi presses.

Storage and Shelf Life

- Store solvents safely within the printing environment to allow them to acclimatize to pressroom conditions – working temperatures will affect evaporation speed of solvents and hence can influence their effectiveness. Consult own company risk assessment and fire risk assessment for guidance on suitable storage containers depending on properties of the chemical.
- If left unopened and kept in the correct conditions this product has a recommended shelf life of 12 months.

Health and Safety

This product is categorized with the following hazardous associations:

GHS02: Flame

GHS07: Exclamation Mark

GHS08: Health hazard

Always wear suitable safety equipment when handling pressroom chemicals. Will not give rise to significant hazard provided good standards of industrial practice are maintained. Consult MSDS for further information.

Available Pack Sizes

5litres, 10litres, 25litres, 205litres.

Note

The information contained in this data sheet corresponds with our current knowledge and experience. The liability for the application and processing of our products lies with the buyer, who is also responsible for observing the third party rights.

We reserve the right to alter any of these details as a result of technical or manufacturing developments.

For any further information please contact the technical department at Uk Euroconnect Ltd