

PLATE DEVELOPERS AND REPLENISHERS FOR ANALOGUE PLATES

CONCENTRATED DEVELOPER FOR ANALOGUE POSITIVE PLATES.

PROPERTIES

- ▶ Weakly buffered. Allows the elimination of film edges without affecting dot reproduction.
- ▶ Its formulation characteristics make it easily miscible with all water types.
- ▶ Reduces calcium residues in the developer bath.

APPLICATION

- ▶ Applicable for all positive plate lines, it is recommended for:
 - ▶ Hand development.
 - ▶ Development in processors with immersion and spray systems.
 - ▶ Tray or dish development.

METHOD OF USE

- | | | |
|------------------------------------|-------------------------|-------------|
| ▶ Advised dilution: | DEVELOPER | REPLENISHER |
| ▶ Plate line TOP F100 | 1+8 | 1+6 |
| ▶ Recommended working temperature: | | |
| ▶ Hand: | 20-22°C | |
| ▶ Processor: | 24 °C ± 1 °C | |
| ▶ Development time: | | |
| ▶ Hand: | 45-60 seconds | |
| ▶ Processor: | 30 ± 5 seconds | |
| ▶ Replenishment rate: | 70-90 ml/m ² | |

CONSIDERATIONS

- ▶ Adequate replenishment keeps filters and circulation systems clean prolonging the life of the bath.
- ▶ Correct cleaning of the equipment will avoid contamination of the new bath and prolong the life of the processor.
- ▶ Clean using **PROCESSOR CLEANER PC-520** and **PROCESSOR CLEANER PC-600**.

PACKAGING

- ▶ 10 litres.
- ▶ 25 litres.
- ▶ 200 litres (with dosing device).

Note:
The results obtained may vary depending if the conditions of use are outside of our recommended values.